# Product datasheet
JUMBO60-3W

**HW/FM small distributor JUMBO Twin**

Order number: 7250070
Type: JUMBO60-3W

Double Power in distribution

- Generous wiring space
- For flush and hollow wall installation
- Ventilation slots in the door for heat dissipation
- Optimal combination of circuit power and communications distribution
- Variants with WiFi door available
- 5-row housing with 2 or 3 row distribution and corresponding communication field
- Two distributors combined into one spacesaving unit

**Dimensions**

| | |
|---|---|
| Depth | 98 mm |
| Height | 900 mm |
| Height of HW cut-out | 860 mm |
| Height of mounting recess | 893 mm |
| Plaster compensation | 15 mm |
| Width | 365 mm |
| Width of HW cut-out | 323 mm |
| Width of mounting recess | 359 mm |

**Material**

| | |
|---|---|
| Box material | PS |
| Cover material | PS |
| Door material | PS / Sheet steel |


© f-tronic GmbH. All rights reserved
www.f-tronic.com

### Properties

| | |
|---|---|
| Can be lead sealed | true |
| Colour | white, similar to RAL 9016 |
| Installation type | |
| Number of compartments | 42 |
| Stackable | true |

### Technical features

| | |
|---|---|
| Suitable for sheet thickness | 8-40 mm |

### Certificates & standards

| | |
|---|---|
| REACH | true |
| RoHS | yes / exception 6c |
| Standards | • DIN EN 60670-1<br>• DIN EN 60670-24<br>• DIN EN 61439-1<br>• DIN EN 61439-3<br>• DIN 43871 |
| VDE | true |

### Accessories

| | |
|---|---|
| Equipped with | 1x door with frame (T+RJUMBO60KW)<br>1x mounting plate<br>1x PE plug-in terminal (SKPE34)<br>1x N-N plug-in terminal (SKN17N)<br>1x socket<br>1x hollow wall anchor set (HWA set) |
| Recommended purchase | Wall claw set (MK-Set)<br>Mounting bracket set (MH-Set)<br>Cover strip (ADS12W) |


© f-tronic GmbH. All rights reserved
www.f-tronic.com