

HW/FM small distributor JUMBO with support frame

Order number: 7250109

Type: JUMBO36+6TS



Preassemblable with System

- Optionally, can be used for flush or hollow wall mounting
- Support frame for easy pre-assembly of devices and equipment
- Generous wiring space
- Strain relief possible
- Packaging can be used as plaster protection
- Suitable with HWA-Set for hollow wall installation (p.119)

Dimensions

| | |
|--------|--------|
| Depth | 98 mm |
| Height | 650 mm |
| Width | 365 mm |

Material

| | |
|----------------|----|
| Box material | PS |
| Cover material | PS |
| Door material | |

Properties

| | |
|---------------------------|-------|
| Can be lead sealed | true |
| Colour | White |
| Degree of protection (IP) | IP30 |
| Installation type | |
| Number of compartments | |
| Number of rows | 3 |
| Stackable | true |

Technical features

| | |
|------------------------------|----------|
| Design current | 63 A |
| Design voltage | 400 V |
| Suitable for sheet thickness | 10-45 mm |

Certificates & standards

| | |
|-------|------|
| REACH | true |
| RoHS | true |
| VDE | true |

Accessories

| | |
|----------------------|---|
| Equipped with | 1x door with frame (T+RJUMBO36+6) 1x PE plug-in terminal (SKPE34) 1x N plug-in terminal (SKN34) 1x N-N plug-in terminal (SKN17N) |
| Recommended purchase | Hollow wall anchor set (HWA-Set) Wall claw set (MK-Set) Mounting bracket set (MH-Set) Cover strip (ADS12W) |