

**Field distributor**

Order number: 7110220

Type: FV2-3



Large distributors for intelligent installation technology

- Generous cable entries at the bottom, top and back of each field width
- Upper and lower cable entry with membrane puncture, allowing quick and easy handling without additional tools
- All covers with lateral bulkheads
- From three field widths with double door
- Various lock variants are possible - even DIN cylinder lock
- Incl. 1x ZSSKN17N and 1x ZSSKPE34 plug-in terminal per field

suitable for:

Dimensions		Environmental conditions	
Depth	165 mm	Ambient temperature (24h)	35 °C
Height	500 mm	Ambient temperature (maximum)	40 °C
Width	550 mm	Ambient temperature (minimum)	-25 °C
		Max. rel. humidity at 25°C (short term)	95 %
		Max. rel. humidity at 40°C	50 %
Material			
Box material	Sheet steel powder-coated		
Cover material	PS		
Door material	Sheet steel powder-coated		

### Properties

Can be lead sealed	-
Colour	White
Degree of protection (IP)	IP43
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Number of bays	2
Number of compartments	72
Number of rows	3
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

### Technical features

Design voltage	400 V
Permissible power loss according to DIN 43 873	

### Certificates & standards

CE	true
Glow wire test	750 °C
REACH	true
RoHS	true
VDE	-

### Accessories

Equipped with	N-Steckklemme 6x25mm <sup>2</sup> ; 28x4mm <sup>2</sup> r PE-Steckklemme 3x25mm <sup>2</sup> ; 14x4mm <sup>2</sup> r 4 x Flansch mit Durchstroßmembran
---------------	--