



Field distributor

Order number: 7110222
Type: FV1-4

- Große Verteiler für die intelligente Installationstechnik
- Großzügige Kabeleinführungen an der Unter-, Ober- und Rückseite je Feldbreite
 - Obere und untere Kabeleinführung mit Durchstoßmembran, dadurch schnelle und einfache Handhabung ohne zusätzliches Werkzeug
 - Alle Abdeckungen mit seitlichen Abschottungen
 - Ab drei Feldbreiten mit Doppeltür
 - Verschiedene Schlossvarianten möglich – auch DIN-Zylinderschloss
 - Inkl. 1x ZSSKN17PE

suitable for:

Dimensions		Environmental conditions	
Depth	165 mm	Ambient temperature (24h)	35 °C
Height	650 mm	Ambient temperature (maximum)	40 °C
Width	300 mm	Ambient temperature (minimum)	-25 °C
		Max. rel. humidity at 25°C (short term)	95 %
		Max. rel. humidity at 40°C	50 %
Material			
Box material	Sheet steel powder-coated		
Cover material	PS		
Door material	Sheet steel powder-coated		

Properties

Can be lead sealed	-
Colour	White
Degree of protection (IP)	IP43
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Number of bays	1
Number of compartments	48
Number of rows	4
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design voltage	400 V
Permissible power loss according to DIN 43 873	

Certificates & standards

CE	true
Glow wire test	750 °C
REACH	true
RoHS	true
VDE	-

Accessories

Equipped with