



Field distributor

Order number: 7110223
Type: FV2-4

Große Verteiler für die intelligente Installationstechnik

- Großzügige Kabeleinführungen an der Unter-, Ober- und Rückseite je Feldbreite
- Obere und untere Kabeleinführung mit Durchstoßmembran, dadurch schnelle und einfache Handhabung ohne zusätzliches Werkzeug
- Alle Abdeckungen mit seitlichen Abschottungen
- Ab drei Feldbreiten mit Doppeltür
- Verschiedene Schlossvarianten möglich – auch DIN-Zylinderschloss
- Inkl. 1x ZSSKN17PE

suitable for:

Dimensions

Depth	165 mm
Height	650 mm
Width	550 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Box material	Sheet steel powder-coated
Cover material	PS
Door material	Sheet steel powder-coated

Properties

Can be lead sealed	-
Colour	White
Degree of protection (IP)	IP43
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Number of bays	2
Number of compartments	96
Number of rows	4
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design voltage	400 V
Permissible power loss according to DIN 43 873	

Certificates & standards

CE	true
Glow wire test	750 °C
REACH	true
RoHS	true
VDE	-

Accessories

Equipped with	PE-N-Steckklemme 3x25mm²; 14x4mm²r 4 x Flansch mit Durchstoßmembran
---------------	--