



Field distributor

Order number: 7110232  
Type: FV4-6

Large distributors for intelligent installation technology

- Generous cable entries at the bottom, top and back of each field width
- Upper and lower cable entry with membrane puncture, allowing quick and easy handling without additional tools
- All covers with lateral bulkheads
- From three field widths with double door
- Various lock variants are possible - even DIN cylinder lock
- Incl. 1x ZSSKN17N and 1x ZSSKPE34 plug-in terminal per field

suitable for:

| Dimensions     |                           | Environmental conditions                |        |
|----------------|---------------------------|-----------------------------------------|--------|
| Depth          | 165 mm                    | Ambient temperature (24h)               | 35 °C  |
| Height         | 950 mm                    | Ambient temperature (maximum)           | 40 °C  |
| Width          | 1050 mm                   | Ambient temperature (minimum)           | -25 °C |
|                |                           | Max. rel. humidity at 25°C (short term) | 95 %   |
|                |                           | Max. rel. humidity at 40°C              | 50 %   |
| Material       |                           |                                         |        |
| Box material   | Sheet steel powder-coated |                                         |        |
| Cover material | PS                        |                                         |        |
| Door material  | Sheet steel powder-coated |                                         |        |

Properties

|                           |                     |
|---------------------------|---------------------|
| Can be lead sealed        | -                   |
| Colour                    | White               |
| Degree of protection (IP) | IP43                |
| Free of heavy metals      | true                |
| Halogen-free              | -                   |
| Installation type         | SM                  |
| Insulation                | Protection class II |
| Number of bays            | 4                   |
| Number of compartments    | 288                 |
| Number of rows            | 6                   |
| PVC-free                  | true                |
| Silicone-free             | true                |
| Stackable                 | true                |
| Weather-resistant         | -                   |

Technical features

|                                                |       |
|------------------------------------------------|-------|
| Design voltage                                 | 400 V |
| Permissible power loss according to DIN 43 873 |       |

Certificates & standards

|                |        |
|----------------|--------|
| CE             | true   |
| Glow wire test | 750 °C |
| REACH          | true   |
| RoHS           | true   |
| VDE            | -      |

Accessories

|               |                                                                                                         |
|---------------|---------------------------------------------------------------------------------------------------------|
| Equipped with | N-Steckklemme 6x25mm²; 28x4mm²r<br>PE-Steckklemme 3x25mm²; 14x4mm²r<br>8 x Flansch mit Durchstoßmembran |
|---------------|---------------------------------------------------------------------------------------------------------|