



Abbildung ähnlich

Distributor cabinet

Order number: 7110245
Type: VS1-7

- Lots of space for maximum distribution
- Housing in an appealing design of 1mm thickness, powder coated steel plate
 - Unique, push-out fastening system, thus rapid and flexible wall mounting
 - Door can be removed without tools and can be affixed to the left or right
 - Large door opening angle
 - Includes cover strips and PE-N plug-in terminals in scope of delivery
 - Retractable mounting rails
 - Large wiring space behind the standard mounting rails
 - Cabinet depth incl. mounting straps 210mm
 - Incl. 1x ZSSKN17N and 1x ZSSKPE34 plug-in terminal per field

suitable for:

Dimensions

Depth	210 mm
Height	1100 mm
Width	300 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Cover material	PS
Door material	Sheet steel powder-coated

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP43
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Number of bays	1
Number of compartments	84
Number of rows	7
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design voltage	400 V
Permissible power loss according to DIN 43 873	

Certificates & standards

CE	true
Glow wire test	750 °C
REACH	true
RoHS	true
VDE	-

Accessories

Equipped with	N-Steckklemme 6x25mm²; 28x4mm²r PE-Steckklemme 3x25mm²; 14x4mm²r 2 x Flansch mit Durchstoßmembran
---------------	---