



Abbildung ähnlich

**Distributor cabinet**

Order number: 7110256  
Type: VS2-9

Lots of space for maximum distribution

- Housing in an appealing design of 1mm thickness, powder coated steel plate
- Unique, push-out fastening system, thus rapid and flexible wall mounting
- Door can be removed without tools and can be affixed to the left or right
- Large door opening angle
- Includes cover strips and PE-N plug-in terminals in scope of delivery
- Retractable mounting rails
- Large wiring space behind the standard mounting rails
- Cabinet depth incl. mounting straps 210mm
- Incl. 1x ZSSKN17N and 1x ZSSKPE34 plug-in terminal per field

suitable for:

**Dimensions**

|        |         |
|--------|---------|
| Depth  | 210 mm  |
| Height | 1400 mm |
| Width  | 550 mm  |

**Environmental conditions**

|                                         |        |
|-----------------------------------------|--------|
| Ambient temperature (24h)               | 35 °C  |
| Ambient temperature (maximum)           | 40 °C  |
| Ambient temperature (minimum)           | -25 °C |
| Max. rel. humidity at 25°C (short term) | 95 %   |
| Max. rel. humidity at 40°C              | 50 %   |

**Material**

|                |                           |
|----------------|---------------------------|
| Cover material | PS                        |
| Door material  | Sheet steel powder-coated |

Properties

|                           |                     |
|---------------------------|---------------------|
| Can be lead sealed        | true                |
| Colour                    | White               |
| Degree of protection (IP) | IP43                |
| Free of heavy metals      | true                |
| Halogen-free              | -                   |
| Installation type         | SM                  |
| Insulation                | Protection class II |
| Number of bays            | 2                   |
| Number of compartments    | 216                 |
| Number of rows            | 9                   |
| PVC-free                  | true                |
| Silicone-free             | true                |
| Stackable                 | true                |
| Weather-resistant         | -                   |

Technical features

|                                                |       |
|------------------------------------------------|-------|
| Design voltage                                 | 400 V |
| Permissible power loss according to DIN 43 873 |       |

Certificates & standards

|                |        |
|----------------|--------|
| CE             | true   |
| Glow wire test | 750 °C |
| REACH          | true   |
| RoHS           | true   |
| VDE            | -      |

Accessories

|               |                                                                                                         |
|---------------|---------------------------------------------------------------------------------------------------------|
| Equipped with | N-Steckklemme 6x25mm²; 28x4mm²r<br>PE-Steckklemme 3x25mm²; 14x4mm²r<br>4 x Flansch mit Durchstoßmembran |
|---------------|---------------------------------------------------------------------------------------------------------|