




Komplettschrank ZE116APZ

Order number: 7120746  
Type: ZE116APZ

- Sammelschienenklemmen (SSK16)
- Sammelschienenisolierung
- Abdeckstreifen (ADS12W)
- 1x N-N-Steckklemme (ZSSKN17N)
- 1x PE-Steckklemme (ZSSKPE34)

Dimensions

|        |         |
|--------|---------|
| Depth  | 210 mm  |
| Height | 1100 mm |
| Width  | 800 mm  |

Environmental conditions

|                                         |        |
|-----------------------------------------|--------|
| Ambient temperature (24h)               | 34 °C  |
| Ambient temperature (maximum)           | 40 °C  |
| Ambient temperature (minimum)           | -25 °C |
| Max. rel. humidity at 25°C (short term) | 95 %   |
| Max. rel. humidity at 40°C              | 50 %   |

Material

|                  |                           |
|------------------|---------------------------|
| Door material    | Sheet steel powder-coated |
| Housing material | Sheet steel powder-coated |

Properties

|                           |                     |
|---------------------------|---------------------|
| Busbars                   |                     |
| Can be lead sealed        | -                   |
| Colour                    | RAL 9016            |
| Degree of protection (IP) | IP31                |
| Free of heavy metals      | true                |
| Halogen-free              | -                   |
| Installation type         | SM                  |
| Insulation                | Protection class II |
| Meter mount               |                     |
| Number of bays            | 3                   |
| Number of meter bays      | 2                   |
| Number of meter spaces    | 2                   |
| Power type                |                     |
| PVC-free                  | true                |
| Silicone-free             | true                |
| Spacing of busbars        | 40 mm               |
| Stackable                 | -                   |
| Weather-resistant         | -                   |
| Wiring                    |                     |

Technical features

|                               |        |
|-------------------------------|--------|
| Cross-section of inlet cable  | 10 mm² |
| Cross-section of outlet cable | 10 mm² |

Certificates & standards

|       |      |
|-------|------|
| CE    | true |
| REACH | true |
| RoHS  | true |
| VDE   | true |

Accessories

Recommended purchase