




Komplettschrank ZE129APZ

Order number: 7121728
Type: ZE129APZ

- Sammelschienenklemmen (SSK16)
- Sammelschienenisolierung
- Abdeckstreifen (ADS12W)
- 1x N-N-Steckklemme (ZSSKN17N)
- 1x PE-Steckklemme (ZSSKPE34)
- 1 x Patchkabel (PL100)
- 2 x Patch-Patch-Verbinder (PPV5)

Dimensions

Depth	210 mm
Height	1100 mm
Width	800 mm

Environmental conditions

Ambient temperature (24h)	34 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Door material	Sheet steel powder-coated
Housing material	Sheet steel powder-coated

Properties

Busbars	
Can be lead sealed	-
Colour	RAL 9016
Degree of protection (IP)	IP31
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Meter mount	
Number of bays	3
Number of meter bays	1
Number of meter spaces	1
Power type	
PVC-free	true
Silicone-free	true
Spacing of busbars	40 mm
Stackable	-
Weather-resistant	-

Technical features

Cross-section of inlet cable	10 mm²
Cross-section of outlet cable	10 mm²

Certificates & standards

CE	true
REACH	true
RoHS	true
VDE	true

Accessories

Recommended purchase