



### ZL452-3-L116-40 - 8Z2R, with ABB pre-automatic machines

Order number: 7199085

Type: ZL452-3-L116-40

- Busbar terminals (SSK35)
- Cover strips (ADS12W)
- Visible bridge 25mm<sup>2</sup>
- LS switch C40A 1-pole 10kA
- Meter plug-in terminal with pins

#### Dimensions

Depth	210 mm
Height	1400 mm
Width	1300 mm

#### Environmental conditions

Ambient temperature (24h)	34
Ambient temperature (maximum)	40
Ambient temperature (minimum)	-25
Max. rel. humidity at 25°C (short term)	95
Max. rel. humidity at 40°C	50

#### Material

Door material	Sheet steel powder-coated
Housing material	Sheet steel powder-coated

### Properties

Busbars	12 x 5 mm
Can be lead sealed	true
Colour	RAL 9016
Degree of protection (IP)	IP54
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Meter mount	3 point mounting
Number of bays	5
Number of meter bays	4
Number of meter spaces	8
Power type	TN-S
PVC-free	true
Silicone-free	true
Spacing of busbars	40
Stackable	-
Weather-resistant	-

### Technical features

Cross-section of inlet cable	16
Cross-section of outlet cable	16

### Certificates & standards

CE	true
REACH	false
RoHS	true / exception 6c
VDE	true

### Accessories

Equipped with	Busbar clamps
---------------	---------------