



FM small distributor JUMBO with screw clamp

Order number: 7210028

Type: UPV12+2ST

Simple and reliable for flush mounting

suitable for:

Dimensions

| | |
|---------------------------|--------|
| Depth | 98 mm |
| Height | 400 mm |
| Height of mounting recess | 393 mm |
| Plaster compensation | 15 mm |
| Width | 365 mm |
| Width of mounting recess | 359 mm |

Material

| | |
|----------------|----|
| Box material | PS |
| Cover material | PS |
| Door material | |

Environmental conditions

| | |
|---|--------|
| Ambient temperature (24h) | 35 °C |
| Ambient temperature (maximum) | 40 °C |
| Ambient temperature (minimum) | -25 °C |
| Max. rel. humidity at 25°C (short term) | 95 % |
| Max. rel. humidity at 40°C | 50 % |

Properties

| | |
|---------------------------|---------------------|
| Can be lead sealed | true |
| Colour | White |
| Degree of protection (IP) | IP30 |
| Free of heavy metals | true |
| Halogen-free | true |
| Installation type | FM |
| Insulation | Protection class II |
| Number of compartments | 14 |
| Number of rows | 1 |
| PVC-free | true |
| Silicone-free | true |
| Stackable | true |
| Weather-resistant | - |

Technical features

| | |
|--|-------|
| Design current | 63 A |
| Design voltage | 400 V |
| Permissible power loss according to DIN 43 873 | |

Certificates & standards

| | |
|----------------|--|
| CE | true |
| Glow wire test | 650 °C |
| REACH | true |
| RoHS | true |
| Standards | <ul style="list-style-type: none">• DIN EN 60670-1• DIN EN 60670-24• DIN EN 61439-1• DIN EN 61439-3• DIN 43871 |
| VDE | true |

Accessories

| | |
|---------------|--|
| Equipped with | 1x door with frame (T+RJUMBO12+2) 1x PE-N screw terminal (KN17PE) |
|---------------|--|