



### FM small distributor JUMBO with screw clamp

Order number: 7210063

Type: UPV60+10ST

Simple and reliable for flush mounting

suitable for:

#### Dimensions

Depth	98 mm
Height	900 mm
Height of mounting recess	893 mm
Plaster compensation	15 mm
Width	365 mm
Width of mounting recess	359 mm

#### Material

Box material	PS
Cover material	PS
Door material	

#### Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

### Properties

Can be lead sealed	true
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	true
Installation type	FM
Insulation	Protection class II
Number of compartments	70
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

### Technical features

Cable entry	backside: 8x M25
Design current	63 A
Design voltage	400 V

### Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
Standards	<ul style="list-style-type: none"><li>• DIN EN 60670-1</li><li>• DIN EN 60670-24</li><li>• DIN EN 61439-1</li><li>• DIN EN 61439-3</li><li>• DIN 43871</li></ul>
VDE	true

### Accessories

Equipped with	1x door with frame (T+RJUMBO60+10) 1x PE screw terminal (KPE34) 2x N-N screw terminal (KN17N)
---------------	---