



HW small distributor JUMBO with screw clamp

Order number: 7230018
Type: HWV48+8ST

Simple and reliable for hollow wall mounting

suitable for:

Dimensions

Depth	98 mm
Height	775 mm
Height of HW cut-out	735 mm
Width	365 mm
Width of HW cut-out	323 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Box material	PS
Cover material	PS
Door material	

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	HW
Insulation	Protection class II
Number of compartments	56
Number of rows	4
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design current	63 A
Design voltage	400 V
Permissible power loss according to DIN 43 873	
Suitable for sheet thickness	10-45 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
Standards	• DIN EN 60670-1 • DIN EN 60670-24 • DIN EN 61439-1 • DIN EN 61439-3 • DIN 43871
VDE	true

Accessories

Equipped with	1x door with frame (T+RJUMBO48+8) 1x PE screw terminal (KPE34) 1x N-N screw terminal (KN17N) 1x hollow wall anchor set (HWA-Set)
Recommended purchase	