



### Damp area small distributor IP65, 1-row

Order number: 7240026

Type: APV4

- Robust design made of impact-resistant plastic
- Interchangeable individual doors in smoke topaz for right and left hinges
- Ideal for difficult installation environments in industrial plants, workshops, basements or garages
- Suitable for applications in protected outdoor areas, depending on the protection class
- For applications in unprotected outdoor areas, the housing must be protected from weather-related stress by installing it in an outdoor housing

suitable for:

#### Dimensions

Depth	120 mm
Height	197 mm
Width	122.5 mm

#### Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

#### Material

Box material	PS
Door material	

### Properties

Can be lead sealed	true
Colour	Grey
Degree of protection (IP)	IP65
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Number of compartments	4
Number of rows	1
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

### Technical features

Design current	63 A
Design voltage	400 V
Total inserts	

### Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
VDE	-

### Accessories

Equipped with	1x cover strip 4TE 1x PE screw terminal 5-pole 1x N screw terminal 5-pole double membrane seals (DMS20 / DMS25)
---------------	--