



HW/FM small distributor JUMBO

Order number: 7250017

Type: JUMBO24+4

Flexible usage - Flush mounted and hollow wall

- Generous wiring space
- Strain relief possible
- Frame height 9mm
- Packaging can be used as plaster protection
- Suitable with HWA-Set for hollow wall installation (sold separately, Art.No. 7290079)

suitable for: Devices up to 63A

Dimensions

Depth	98 mm
Height	525 mm
Height of HW cut-out	485 mm
Height of mounting recess	518 mm
Plaster compensation	15 mm
Width	365 mm
Width of HW cut-out	323 mm
Width of mounting recess	359 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Box material	PS
Cover material	PS
Door material	Powder-coated steel

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Impact resistance	IK07
Installation type	HW / UP
Insulation	Protection class II
Number of compartments	28
Number of rows	2
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design current	63 A
Design voltage	400 V
Permissible power loss according to DIN 43 873	without inner horizontal partitions 10 K = 6.5 watts 15 K = 11.0 watts 20 K = 15.0 watts 25 K = 20.0 watts 30 K = 25.0 watts
Suitable for sheet thickness	10-45 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	false
RoHS	true
Standards	<ul style="list-style-type: none"> • DIN EN 60670-1 • DIN EN 60670-24 • DIN EN 61439-1 • DIN EN 61439-3 • DIN 43871
VDE	true

Accessories

Equipped with	1x door with frame (T+RJUMBO24+4) 1x FI additional terminal (FIK) 1x PE-N plug-in terminal (SKN17PE)
Recommended purchase	Hollow wall anchor set (HWA-Set) Wall claw set (MK-Set) Mounting bracket set (MH-Set) Cover strip (ADS12W)