



**HW/FM communications distributor JUMBO K**

Order number: 7250063  
Type: JUMBO60K

Innovative solutions for communications distribution

- For hollow wall and flush installation
- For installation of multimedia applications (e.g. : Telecommunications and CATV distribution)
- Convenient access to hardware components (e.g. : modem, wireless router, switch)
- Standard 3-way socket with staggered slots
- Ventilation slots in the door for heat dissipation

suitable for:

**Dimensions**

Depth	98 mm
Height	900 mm
Height of HW cut-out	860 mm
Height of mounting recess	893 mm
Plaster compensation	15 mm
Width	365 mm
Width of HW cut-out	323 mm
Width of mounting recess	359 mm

**Environmental conditions**

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

**Material**

Box material	PS
Cover material	PS
Door material	Sheet steel powder-coated

### Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	HW / UP
Insulation	Protection class II
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

### Technical features

Design current	63 A
Design voltage	400 V
Suitable for sheet thickness	10-45 mm

### Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
VDE	-

### Accessories

Equipped with	<ul style="list-style-type: none"> <li>1x door with frame (T+RJUMBO60K)</li> <li>1x Patch-panel (PATCH12)</li> <li>4x mounting plate</li> <li>1x 3-way socket (STECKD3)</li> <li>1x hollow wall anchor set (HWA-Set)</li> <li>1x connection bracket (VK-Set)</li> </ul>
Recommended purchase	<ul style="list-style-type: none"> <li>Wall claw set (MK-Set)</li> <li>Mounting bracket set (MH-Set)</li> </ul>