



HW/FM communications distributor JUMBO KW

Order number: 7250064
Type: JUMBO36KW

Innovative solutions for communications distribution

- For hollow wall and flush installation
- For installation of multimedia applications (e.g. : telecommunications and CATV distribution)
- Convenient access to hardware components (e.g.: modem, wireless router, switch)
- Standard 3-way socket with staggered slots
- Ventilation slots in the door for heat dissipation
- Door with plastic insert for WiFi application

suitable for:

Dimensions

Depth	98 mm
Height	650 mm
Height of HW cut-out	610 mm
Height of mounting recess	643 mm
Plaster compensation	15 mm
Width	365 mm
Width of HW cut-out	323 mm
Width of mounting recess	359 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Box material	PS
Cover material	PS
Door material	PS / Sheet steel

Properties

Can be lead sealed	true
Colour	white, similar to RAL 9016
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	HW / UP
Insulation	Protection class II
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design current	63 A
Design voltage	400 V
Suitable for sheet thickness	10-45 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
VDE	-

Accessories

Equipped with	1x door with frame (T+RJUMBO36KW) 1x patch panel (PATCH12) 2x mounting plate 1x 3-way socket (STECKD3) 1x hollow wall anchor set (HWA set) 1x connecting clip (VK set)
Recommended purchase	Wall claw set (MK-Set) Mounting bracket set (MH-Set)