



FM Device socket box, solid

Order number: 7310104

Type: UP40

Versatile applications - Solid construction

- Extremely solid material, high wall thickness
- Flexible installation by variable dividers

Dimensions

| | |
|----------------|------------|
| Depth | 63 - 63 mm |
| Height | 71 mm |
| Internal depth | 62 mm |
| Length | 71 mm |
| Width | 284 mm |

Environmental conditions

| | |
|---|--------|
| Ambient temperature (24h) | 35 °C |
| Ambient temperature (maximum) | 40 °C |
| Ambient temperature (minimum) | -25 °C |
| Max. rel. humidity at 25°C (short term) | 90 % |
| Max. rel. humidity at 40°C | 50 % |

Properties

| | |
|---------------------------|-------|
| Can be lead sealed | - |
| Colour | Black |
| Degree of protection (IP) | IP20 |
| Free of heavy metals | true |
| Halogen-free | true |
| Installation type | FM |
| PVC-free | true |
| Silicone-free | true |
| Stackable | - |
| Weather-resistant | - |

Technical features

| | |
|--------------------------------|---------------------|
| Cable entry flat cable 20x10mm | 28 |
| Design voltage | 400 V |
| max. cross section | 2,5 mm ² |
| Pipe entry M20 | 18 |

Certificates & standards

| | |
|----------------|--------|
| CE | true |
| Glow wire test | 650 °C |
| REACH | false |
| RoHS | true |
| VDE | - |

Accessories

| | |
|---------------|------|
| Equipped with | None |
|---------------|------|