



UP Gerätedose E106M25S

Order number: 7310129
Type: E106M25

- The basics for a good FM installation
- Flexibly combined with all FM socket boxes
 - 20 and 25mm pipe insertion
 - 4x screw boss and 2x area for spreader claw springs

Dimensions	
Depth	46 - 46 mm
Internal depth	45 mm
Length	80 mm
Width	66 mm

Environmental conditions	
Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Material	
Socket material	PS

Properties

Can be lead sealed	-
Colour	Black
Degree of protection (IP)	IP20
Free of heavy metals	true
Halogen-free	true
Installation type	FM
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Cable entry	4
Design voltage	400 V
max. cross section	2,5 mm²
Pipe entry M20	7
Pipe entry M25	2

Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
Standards	• DIN EN 60670-1(VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None
---------------	------