



Damp area distribution box E1210

Order number: 7340160
Type: E1210ws

Easy to use - Stable execution

- Easy to install
- Easy to use - no need for expensive, additional tools
- With integrated push-out membranes on all four sides
- With back side membrane introduction for cables of up to 5x 2.5mm²
- Execution with and without fixing straps

Dimensions		Environmental conditions	
Depth	37 mm	Ambient temperature (24h)	35 °C
Length	80 mm	Ambient temperature (maximum)	40 °C
Width	80 mm	Ambient temperature (minimum)	-25 °C
		Max. rel. humidity at 25°C (short term)	90 %
		Max. rel. humidity at 40°C	50 %
Material			
Housing material	PP/TPE		
Lid material	PE		

Properties

Colour	White
Degree of protection (IP)	IP55
Halogen-free	true
Installation type	SM
Insulation	Protection class II
Silicone-free	true

Technical features

Cable entry 7x1.5²/5x2.5²	12
Design voltage	400 V
Ground inserts	2
max. cross section	2,5 mm²

Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
Standards	- DIN EN 60670-1 (VDE 0606-1) - DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None
---------------	------