
# Product datasheet
E115



## HW Device socket E115

Order number: 7350094
Type: E115

The basics for a proper hollow wall installation

- With break-outs for cables and pipes
- Integrated pipe support for NYM cables
- Secure fixing of tubes

### Dimensions

| | |
|---|---|
| Depth | 47 - 47 mm |
| Diameter | 68 mm |
| Internal depth | 46 mm |
| Milling hole diameter | Ø 68 mm |

### Environmental conditions

| | |
|---|---|
| Ambient temperature (24h) | 35 °C |
| Ambient temperature (maximum) | 40 °C |
| Ambient temperature (minimum) | -25 °C |
| Max. rel. humidity at 25°C (short term) | 90 % |
| Max. rel. humidity at 40°C | 50 % |

### Material

| | |
|---|---|
| Socket material | PP |


© f-tronic GmbH. All rights reserved
www.f-tronic.com

### Properties

| | |
|---|---|
| Can be lead sealed | - |
| Colour | Orange |
| Degree of protection (IP) | IP30 |
| Free of heavy metals | true |
| Halogen-free | - |
| Installation type | HW |
| PVC-free | true |
| Silicone-free | true |
| Stackable | - |
| Weather-resistant | - |

### Technical features

| | |
|---|---|
| Cable entry 3x1.5² | 2 |
| Cable entry 5x1.5²/3x2.5² | 2 |
| Design voltage | 400 V |
| max. cross section | 2,5 mm² |
| Pipe entry M20 | 2 |
| Suitable for sheet thickness | 5-40 mm |

### Certificates & standards

| | |
|---|---|
| CE | true |
| Glow wire test | 850 °C |
| REACH | true |
| RoHS | true |
| Standards | • DIN EN 60670-1(VDE 0606-1)<br>• DIN EN 60670-22 (VDE 0606-22) |
| VDE | true |

### Accessories

| | |
|---|---|
| Equipped with | None |


© f-tronic GmbH. All rights reserved
www.f-tronic.com