



**HW LAN socket E5100HF**

Order number: 7360055

Type: E5100HF

The specialist for your IT applications

- Compliance with bending radii for network and data lines
- Combinable
- 3x cable entry for Simplex or Duplex
- Guaranteed airtight
- Milling hole Ø 68mm

**Dimensions**

Depth	60 - 60 mm
Diameter	68 mm
Milling hole diameter	Ø 68 mm

**Environmental conditions**

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

**Material**

Socket material	PP/TPE
-----------------	--------

### Properties

Can be lead sealed	-
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	true
Installation type	HW
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

### Technical features

Cable entry	2
Cable entry duplex	1
Cable entry network cable	2
Design voltage	400 V
Suitable for sheet thickness	5-25 mm

### Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
Standards	<ul style="list-style-type: none"> <li>• DIN EN 60670-1 (VDE 0606-1)</li> <li>• DIN EN 60670-22 (VDE 0606-22)</li> </ul>
VDE	true

### Accessories

Equipped with	None
---------------	------