



HW Device connection socket E3700TC for timber construction

Order number: 7360072 Type: E3700TC

Installation boxes - Fixed in timber construction

- Installation box with robust housing
- Fastening by means of TC claws that anchor themselves in the wood
- Airtight due to 2-component membrane technology
- Easy to install due to tool-free cable and pipe entry
- Integrated cable restraint for NYM cables
- Cost-effective, standard-compliant solution for solid wood, cross-laminated timber and hybrid constructions
- Simple and quick assembly

| Dimensions | |
|-----------------------|------------|
| Depth | 62 - 62 mm |
| Diameter | 68 mm |
| Internal depth | 60 mm |
| Milling hole diameter | Ø 68 mm |

Product datasheet

E3700TC



| Properties | | Technical features | |
|---------------------------|--------|--|---------|
| Colour | Orange | Cable entry 3x1.5 ² | 2 |
| Degree of protection (IP) | IP30 | Cable entry 5x1.5 ² /3x2.5 ² | 2 |
| | | max. cross section | 2,5 mm² |
| | | Pipe entry ≤M25 | 2 |
| | | Suitable for sheet thickness | ≥ 10 mm |
| | | Certificates & standards | |
| | | REACH | true |
| | | RoHS | true |
| Accessories | | | |
| | | | None |
| Equipped with | | | None |