



HW Sound protection socket SP3700HF

Order number: 7520002
Type: SP3700HF

Relaxes and provides privacy

- Sound-absorbing function of the wall remains intact
- Subsequent installation possible
- Airtight with 2K membrane technology
- 4 cable entries
- 2x M25 pipe entries
- Installation of up to 5-fold combinations possible
- Opposing installation from 120mm wall thickness possible

Dimensions

Depth	58 - 58 mm
Diameter	68 mm
Milling hole diameter	Ø 68 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Material

Socket material	PP/TPE
-----------------	--------

Properties

Can be lead sealed	-
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	true
Installation type	HW
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

Technical features

Cable entry 3x1.5²	2
Cable entry 5x1.5²/3x2.5²	2
Design voltage	400 V
max. cross section	2,5 mm²
Pipe entry ≤M25	2
Suitable for sheet thickness	5-40 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
Standards	• Measurement of airborne sound insulation after DIN EN ISO 10 140 • DIN EN 60670-1 (VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None
---------------	------