



Sealing plug, airtight

Order number: 9930018  
Type: E10

Tested to be airtight - Energy efficiency for FM & HW

- For all flexible insulating pipes
- Can be used subsequently for airtight sealing of pipes
- Simple and reliable
- Can be optimally used in combination with airtight installation boxes

suitable for:

| Dimensions |     | Environmental conditions                |        |
|------------|-----|-----------------------------------------|--------|
| Diameter   | M40 | Ambient temperature (24h)               | 35 °C  |
|            |     | Ambient temperature (maximum)           | 40 °C  |
|            |     | Ambient temperature (minimum)           | -25 °C |
|            |     | Max. rel. humidity at 25°C (short term) | 90 %   |
|            |     | Max. rel. humidity at 40°C              | 50 %   |

Properties

|                      |      |
|----------------------|------|
| Can be lead sealed   | -    |
| Colour               | Grey |
| Free of heavy metals | true |
| Halogen-free         | true |
| PVC-free             | true |
| Silicone-free        | true |
| Stackable            | -    |
| Weather-resistant    | -    |

Technical features

|                     |       |
|---------------------|-------|
| Max. Cable diameter | 25 mm |
|---------------------|-------|

Certificates & standards

|                |        |
|----------------|--------|
| CE             | -      |
| Glow wire test | 850 °C |
| REACH          | true   |
| RoHS           | true   |
| VDE            | -      |