Product data sheet

E106M25

FM Device Box E106M25, d=46mm

Product No.: 7310129

Type: E106M25

The basics for a good FM installation
- Flexibly combined with all FM socket boxes
- 20 and 25mm pipe insertion
- 4x screw boss and 2x area for spreader claw springs

Measures	
Depth	46 mm

Material	
Socket material	PS

Environmental conditions	
Ambient temperature (minimum)	-25 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (24h)	35 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Technical features	
Max. cross section	2,5 mm²
Design voltage	400 V
Cable entry	4
Pipe entry M20	7
Pipe entry M25	2

© f-tronic GmbH. All rights reserved
www.f-tronic.de

Product data sheet

E106M25

Certificates & Standards	
VDE	true
CE	true
Glow wire test	650 °C
REACH	false
RoHS	true
Standards	• DIN EN 60670-1(VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)

Properties	
Installation type	FM
Degree of protection (IP)	IP20
Stackable	true
Halogen-free	true
Free of heavy metals	true
PVC-free	true
Silicone-free	true

© f-tronic GmbH. All rights reserved
www.f-tronic.de