Product data sheet

JUMBO60-2W

HW/FM small distributor Twin, Jumbo60-2W, 2-row, 24+4 Mod, incl. mounting plate, wireless door

Product No.: 7250069

Type: JUMBO60-2W

Double Power in distribution
- Generous wiring space
- For flush and hollow wall installation
- Ventilation slots in the door for heat dissipation
- Optimal combination of circuit power and communications distribution
- Variants with WiFi door available
- 5-row housing with 2 or 3 row distribution and corresponding communication field
- Two distributors combined into one spacesaving unit

Measures	
Height	900 mm
Width	365 mm
Depth	98 mm
Height of HW cut-out	860 mm
Width of HW cut-out	323 mm
Height of mounting recess	893 mm
Width of mounting recess	359 mm
Installation height T+R	9 mm
Plaster compensation	15 mm

Material	
Box material	PS
Door material	PS / Sheet steel
Cover material	PS

© f-tronic GmbH. All rights reserved
www.f-tronic.de

Product data sheet

JUMBO60-2W

Accessories

Equipped with	1x door with frame (T+RJUMBO60-2W) 2x mounting plate 1x PE-N plug-in terminal (SKN17PE) 1x socket 1x hollow wall anchor set (HWA set)
Recommended purchase	Wall claw set (MK-Set) Mounting bracket set (MH-Set) Cover strip (ADS12W)

Technical features

Suitable for sheet thickness	8-40 mm

Certificates & Standards

VDE	true
Glow wire test	850 °C
REACH	false
RoHS	true / exception 6c
Standards	• DIN EN 60670-1 • DIN EN 60670-24 • DIN EN 61439-1 • DIN EN 61439-3 • DIN 43871

Properties

Installation type	HW/UP
Colour	white, similar to RAL 9016
Impact resistance	IK07
Number of compartments	28
Stackable	true
Can be lead sealed	true

© f-tronic GmbH. All rights reserved
www.f-tronic.de