Product data sheet

JUMBO60KW

HW/FM communication distributor 5r, Jumbo60KW, with wireless door, patch panel, 3-way socket

Product No.: 7250066

Type: JUMBO60KW

Innovative solutions for communications distribution
- For hollow wall and flush installation
- For installation of multimedia applications (e.g .: telecommunications and CATV distribution)
- Convenient access to hardware components (e.g.: modem, wireless router, switch)
- Standard 3-way socket with staggered slots
- Ventilation slots in the door for heat dissipation
- Door with plastic insert for WiFi application

Measures	
Height	900 mm
Width	365 mm
Depth	98 mm
Height of HW cut-out	860 mm
Width of HW cut-out	323 mm
Height of mounting recess	893 mm
Width of mounting recess	359 mm
Installation height T+R	9 mm
Plaster compensation	15 mm

Material	
Box material	PS
Door material	PS / Sheet steel
Cover material	PS

© f-tronic GmbH. All rights reserved
www.f-tronic.de

Product data sheet

JUMBO60KW

Environmental conditions

Ambient temperature (minimum)	-25 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (24h)	35 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Technical features

Suitable for sheet thickness	10-45 mm
Design voltage	400 V
Design current	63 A

Properties

Installation type	HW / UP
Colour	white, similar to RAL 9016
Degree of protection (IP)	IP30
Insulation	Protection class II
Impact resistance	IK07
Stackable	true
Can be lead sealed	true
Free of heavy metals	true
PVC-free	true
Silicone-free	true

Accessories

Equipped with	1x door with frame (T+RJUMBO60KW) 1x patch panel (PATCH12) 4x mounting plate 1x 3-way socket (STECKD3) 1x hollow wall anchor set (HWA set) 1x connecting clip (VK set)
Recommended purchase	Wall claw set (MK-Set) Mounting bracket set (MH-Set)

Certificates & Standards

CE	true
Glow wire test	850 °C
REACH	false
RoHS	true

© f-tronic GmbH. All rights reserved
www.f-tronic.de