NEPTUN Compact

Small size. Great resistance.











NEPTUN Compact

Small size. Great resistance.

The distribution box series for safe installation in damp areas.

A new member of the NEPTUN family: The new damp area distribution box series NEPTUN Compact. The strong NFK series boxes are the perfect addition to the NEPTUN damp area distributor range. Together the product family ensures a safe electrical installation in damp areas or protected outdoor areas. The NEPTUN Compact boxes come in a modern design and are available in four sizes. With the IP66 protection class the NFK series also safely protects wiring against the entrance of water and dust.

Sounds interesting? Then discover the new range as well as the additional highlights of the NEPTUN Compact series, such as the screw closure with an assembly position, external tabs as standard, covers with an extra-flat design and many more.







Sturdy closure

In no time at all

The screw closures with assembly position can be opened and closed with a ¼ turn. This position prevents the screws falling out or turning unintentionally. These screws enable fast assembly and dismantling. If required, the NEPTUN Compact series can be sealed on the opposite corners as standard.





Resists water and dust

Reliable all-round protection

The boxes are **sealed all-round**. This prevents the entrance of dust and water. This allows protection class IP66 to be fulfilled. The high degree of protection and strength makes the distribution boxes suitable for installation in protected outdoor areas. The NEPTUN Compact series provides robust protection against a wide range of weather conditions.









Hardly surpassable in variety

Break-out entries M20-M40

The distribution boxes have **different**, **pre-punched break-out entries**. This allows cables and wires to be routed into various entries as required, from M20 to M40. The cable entry can be customised using the break-out entries. Either using the double membrane seals provided, which guarantee IP65 protection class or using a cable gland (provides strain relief and fastens the inserted cable).



Practical and time-saving

Membrane entry on NFK08

The most compact model, the NFK08, is already equipped with **membrane entries** instead of break-out openings. This allows cables and wires to be inserted quickly, without tools and without additionally installing double membrane seals. When using cable glands, the membrane is simply cut out fully and the opening can be used for a gland.











Invisible hold

Internal fixing with insulating plugs


For the internal mounting of the box, the transverse and elongated hole cut-outs allow an successfull invisible wall mounting. To maintain the protection class IP66, the screw connection to the wall must be sealed with the insulating plugs supplied.



Perfect alignment

With external mounting tabs

The distribution box can also be mounted with **external mounting tabs**. This allows retrospective alignment, since the external tabs have transverse and elongated holes. These are already supplied on delivery and can be used as required.









Noticeably unnoticeable

Flat cover for universal mounting

The flat design of the NEPTUN Compact series means that it is ideally suited to mounting additional components. This allows, for example, switches and plugs to be installed easily in protected outdoor areas. With the flat surface, a multitude of different components can be attached universally.









































NEPTUN Compact Small size. Great resistance.









Туре	NFK08gr	NFK11gr	NFK14gr	NFK18gr
Execution	Damp area distribution box	Damp area distribution box	Damp area distribution box	Damp area distribution box
Item No.	7340190	7340191	7340192	7340193
SU/CB/PL	1 / 72 / 2.304	1 / 36 / 1.152	1 / 20 / 640	1 / 12 / 384
H x W x D	85 x 85 x 54 mm	110 x 110 x 67mm	140 x 140 x 81 mm	180 x 180 x 93 mm
Material	PS	PS	PS	PS
Max. cross section	4 mm²	6 mm²	10 mm²	16 mm²
Entry ≤ M20	7	-	-	-
Entry M20	-	2	2	2
Entry M20 / M25	-	7	5	2
Entry M25 / M32	-	-	5	5
Entry M25 / M32 / M40	-	-	-	5
Colour	grey	grey	grey	grey
Equipped with	2x external mounting tab	3x double membrane seal M20 (DMS20), 2x double membrane seal M25 (DMS25), 2x screw cover, 2x external mounting tab	2x double membrane seal M20 (DMS20), 2x double membrane seal M25 (DMS25), 2x double membrane seal M32 (DMS32), 4x screw cover, 2x external mounting tab	2x double membrane seal M20 (DMS20), 2x double membrane seal M25 (DMS25), 3x double membrane seal M32 (DMS32), 4x screw cover, 2x external mounting tab











Туре	NFK08ws	NFK11ws	NFK14ws	NFK18ws
Execution	Damp area distribution box	Damp area distribution box	Damp area distribution box	Damp area distribution box
Item No.	7340198	7340199	7340200	7340201
SU/CB/PL	1 / 72 / 2.304	1 / 36 / 1.152	1 / 20 / 640	1 / 12 / 384
H x W x D	85 x 85 x 54 mm	110 x 110 x 67mm	140 x 140 x 81 mm	180 x 180 x 93 mm
Material	PS	PS	PS	PS
Max. cross section	4 mm²	6mm²	10mm²	16mm²
Entry ≤M20	7	-	-	-
Entry M20	-	2	2	2
Entry M20 / M25	-	7	5	2
Entry M25 / M32	-	-	5	5
Entry M25 / M32 / M40	-	-	-	5
Colour	white	white	white	white
Equipped with	2x external mounting tab	3x double membrane seal M20 (DMS20ws), 2x double membrane seal M25 (DMS25ws), 2x screw cover, 2x external mounting tab	2x double membrane seal M20 (DMS20ws), 2x double membrane seal M25 (DMS25ws), 2x double membrane seal M32 (DMS32ws), 4x screw cover, 2x external mounting tab	2x double membrane seal M20 (DMS20ws), 2x double membrane seal M25 (DMS25ws), 3x double membrane seal M32 (DMS32ws), 4x screw cover, 2x external mounting tab





IP66 damp area distribution box for safety lighting



Accessories



Save time during installation

Cable & wire entry via double membrane seals







Туре	DMS20	DMS25	DMS32
Execution	Double membrane seal M20	Double membrane seal M25	Double membrane seal M32
Item no.	7290059	7290060	7290061
SU/CB/PL	20 / 1.000 / 64.000	20 / 800 / 51.200	20 / 600 / 38.400
Material	PVC	PVC	PVC
Colour	grey	grey	grey
Cable diameter	Ø 7 - 12mm	Ø 12 - 18mm	Ø 14 - 23mm







Туре	DMS20ws	DMS25ws	DMS32ws
Execution	Double membrane seal M20	Double membrane seal M25	Double membrane seal M32
Item no.	7290223	7290224	7290225
SU/CB/PL	20 / 1.000 / 64.000	20 / 800 / 51.200	20 / 600 / 38.400
Material	PVC	PVC	PVC
Colour	white	white	white
Cable diameter	Ø 7 - 12mm	Ø 12 - 18mm	Ø 14 - 23mm










Туре	NFK08SB	NFK11SB	NFK14SB	NFK18SB
Execution	Damp area distribution box for safety lighting	Damp area distribution box for safety lighting	Damp area distribution box for safety lighting	Damp area distribution box for safety lighting
Item No.	7340210	7340211	7340212	7340213
SU/CB/PL	1 / 72 / 2.304	1 / 36 / 1.152	1 / 20 / 640	1 / 12 / 384
H x W x D	85 x 85 x 54 mm	110 x 110 x 67mm	140 x 140 x 81 mm	180 x 180 x 93 mm
Material	PS	PS	PS	PS
Max. cross section	4 mm²	6 mm²	10 mm²	16 mm²
Entry ≤M20	7	-	-	-
Entry M20	-	2	2	2
Entry M20 / M25	-	7	5	2
Entry M25 / M32	-	-	5	5
Entry M25 / M32 / M40	-	-	-	5
Colour	grey / red	grey / red	grey / red	grey / red
Equipped with	2x external mounting tab	3x double membrane seal M20 (DMS20), 2x double membrane seal M25 (DMS25), 2x screw cover, 2x external mounting tab	2x double membrane seal M20 (DMS20), 2x double membrane seal M25 (DMS25), 2x double membrane seal M32 (DMS32), 4x screw cover, 2x external mounting tab	2x double membrane seal M20 (DMS20), 2x double membrane seal M25 (DMS25), 3x double membrane seal M32 (DMS32), 4x screw cover, 2x external mounting tab

18





NEPTUN Compact

Small size. Great resistance.

- · Robust housing in a modern design
- · Screws with assembly position
- Various break-out entries M20-M40
- IP66 protection class with all-round seal
- Custom fixing options for perfect alignment (external tabs included in scope of supply)
- Membrane entry on NFK08
- 4 different sizes





Legend and register

Register

Туре	Item No.	Page	Item No.	Туре	Page
DMS20	7290059	19	7290059	DMS20	19
DMS20ws	7290223	19	7290060	DMS25	19
DMS25	7290060	19	7290061	DMS32	19
DMS25ws	7290224	19	7290223	DMS20ws	19
DMS32	7290061	19	7290224	DMS25ws	19
DMS32ws	7290225	19	7290225	DMS32ws	19
NFK08gr	7340190	16	7340190	NFK08gr	16
NFK08SB	7340210	18	7340191	NFK11gr	16
NFK08ws	7340198	17	7340192	NFK14gr	16
NFK11gr	7340191	16	7340193	NFK18gr	16
NFK11SB	7340211	18	7340198	NFK08ws	17
NFK11ws	7340199	17	7340199	NFK11ws	17
NFK14gr	7340192	18	7340200	NFK14ws	17
NFK14SB	7340212	18	7340201	NFK18ws	17
NFK14ws	7340200	17	7340210	NFK08SB	18
NFK18gr	7340193	16	7340211	NFK11SB	18
NFK18SB	7340213	18	7340212	NFK14SB	18
NFK18ws	7340201	17	7340213	NFK18SB	18

Legend

Surfac

Surface mounted

©VE

VDE certification

C€

CE marking

IP 66

IP classification

Protection class II

650 C

Glow wire test

HALOGE FREE

Halogen-free

Imprint:

© f-tronic® GmbH 2022

Sources for images:

© kubais - stock.adobe.com (p.1),© lovelyday12 - stock. adobe.com (p.2-3), © Michael Sapryhin - stock.adobe.com(p. 2-3), © tektur - stock.adobe.com (p. 14), © sveta - stock. adobe.com (p.14), © js-photo - stock.adobe.com (p.14), © runzelkorn - stock.adobe.com (p.14), © schlierner - stock. adobe.com (p. 15), © Iriana Shiyan - stock.adobe.com (p. 15), © Mathias Weil - stock.adobe.com (p.15) © GM Photography - stock.adobe.com (p.15),

© peshkova - stock.adobe.com (p.20) © denisismagilov - stock.adobe.com (p. 23) Contact



Do you need specific advice?

Our highly competent team is there for you.

Tel.:+49 6893 9483-0

More information at: www.f-tronic.com



f-tronic® GmbH Zum Gerlen 21-25 D-66131 Saarbrücken Phone +49 6893 9483-0 Fax +49 6893 9483-94 E-Mail info@f-tronic.de

Brochure status: 04.2022 Item No.: 1510115 Layout and design f-tronic* GmbH Note: we reserve the right to make technical changes or modify the contents of this document at any time without prior notice. When ordering, the particulars shall prevail. **f-tronic*** assumes no responsibility for any errors or omissions in this document. We reserve all rights in this document and in the subject matter and illustrations contained therein. Reproduction or use of its contents is prohibited without the prior, written consent of **f-tronic***.

Copyright © 2022 **f-tronic*** All rights reserved.